

ULTRA TORQUE™

4" Canned Submersible Motors

High efficiency, durable motor with outstanding electrical performance.

- NEMA Mounting Dimensions
- Insulation: Class F
- Canned Type Hermetically Sealed Stator
- All Stainless Steel Construction
- Removable Motor Lead
- Resin System-Water Lubrication
- Filter Check Valve
- Kingsbury Type Thrust Bearing
- Pressure Equalizing Diaphragm
- All motors prefilled and 100% tested

2-Wire Single Phase

Model	Rating					Full Load		Max S.F. Load		EFF%		P.F.%		Locked Amps	Length	Weight	Cable Length
	HP	KW	Volts	HZ	S.F.	A	W	A	W	S.F.	F.L.	S.F.	F.L.	A	Inch	Lbs	Inch
4SF05-2W1	0.5	0.37	115	60	1.6	6.8	725	9.0	990	62	54	96	92	34	11.5	19.8	48.0
4SF05-2W2	0.5	0.37	230	60	1.6	3.4	730	4.3	960	62	51	97	92	18	11.5	19.8	48.0
4SF07-2W2	0.75	0.55	230	60	1.5	4.7	998	5.8	1300	61	56	95	92	25	12.6	23.6	48.0
4SF10-2W2	1	0.75	230	60	1.4	6.2	1306	7.5	1650	63	57	95	91	33	13.7	26.2	48.0
4SF15-2W2	1.5	1.1	230	60	1.3	9.0	1931	10.5	2300	65	62	97	95	45	15.6	26.2	48.0

3-Wire Single Phase

Model	Rating					Full Load		Max S.F. Load		EFF%		P.F.%		Locked Amps	Length	Weight	Cable Length
	HP	KW	Volts	HZ	S.F.	A	W	A	W	S.F.	F.L.	S.F.	F.L.	A	Inch	Lbs	Inch
4SF05-3W1	0.5	0.37	115	60	1.6	Y10.6 B10.6 R0	796	Y12.6 B12.6 R0	1120	54	50	76	62	46	9.5	17.9	48.0
4SF05-3W2	0.5	0.37	230	60	1.6	Y5.3 B5.3 R0	796	Y6.3 B6.3 R0	1120	54	50	76	62	23	9.5	17.9	48.0
4SF07-3W2	0.75	0.55	230	60	1.5	Y6.9 B6.9 R0	1141	Y8.3 B8.3 R0	1550	61	56	75	64	32	10.6	19.8	48.0
4SF10-3W2	1	0.75	230	60	1.4	Y8.2 B8.2 R0	1412	Y9.8 B9.8 R0	1825	63	57	73	62	39	11.7	22.9	48.0
4SF15-3W2	1.5	1.1	230	60	1.3	Y10.8 B10.4 R0.8	1994	Y12.3 B12 R1	2390	65	62	86	82	46	13.6	29.1	60.0
4SF20-3W2	2	1.5	230	60	1.15	Y10.8 B10.5 R2.8	2236	Y13.2 B12 R2.8	2453	70	66	93	92	54	15.1	32.2	60.0
4SF30-3W2	3	2.25	230	60	1.15	Y15 B11.5 R6.5	3530	Y17.8 B13 R7	4035	69	69	97	97	85	20.9	50.7	80.0
4SF50-3W2	5	3.75	230	60	1.15	Y24.5 B16 R11	5770	Y28.5 B19 R11	6634	69	69	98	98	120	27.0	86.0	80.0



Swiss Pacific, Inc. • 4160 Weaver Court South • Hilliard, Ohio • 43026

800-770-3860

www.SwissPacific.com